



MATERIAL:
 BODY: STAINLESS STEEL
 CONTACT: BERYLLIUM COPPER
 INSULATOR: NORYL/PTFE

PERFORMANCE:
 IMPEDANCE: 50 OHMS
 FREQUENCY: DC TO 18GHz
 VSWR: <1.20

THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION THAT CANNOT BE REPRODUCED OR DIVULGED, IN WHOLE OR IN PART, WITHOUT WRITTEN AUTHORIZATION FROM "LANJIAN ELECTRONICS"

MATERIAL :		UNLESS OTHERWISE SPECIFIED: DIMENSIONS IN MM	
TOLERANCES :			
X.X	±0.20	ANGULAR :	±1°
X.XX	±0.10	FILLETS R/C :	±0.10
X.XXX	±0.01	SURFACE FINISH :	Ra 1.6
			DEBURR AND BREAK SHARP EDGES
DRAWN	NAME	DATE	SIGNATURE
CHK'D	X.C.W	04/13/2021	
APP'VD	H.Z.Y	04/13/2021	
MFG			
PROJECTION	SIZE	SCALE	
	A3	8:1	

LANJIAN ELECTRONICS
 38 Hengtong Road, Xinqu Dingmao
 Zhenjiang, 212009, Jiangsu, P. R. China

TITLE: **2.4/N-KK**

DWG No. GCP Z3.640.0.025

REV. **A**

DO NOT SCALE THE DRAWING

PAGE 1 / 1