



MATERIAL:
 BODY: STAINLESS STEEL
 CONTACT: BERYLLIUM COPPER
 INSULATOR: PEI

PERFORMANCE:
 IMPEDANCE: 50 OHMS
 FREQUENCY: DC TO 110 GHZ
 VSWR: ≤1.50

THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION THAT CANNOT BE REPRODUCED OR DIVULGED, IN WHOLE OR IN PART, WITHOUT WRITTEN AUTHORIZATION FROM "LANJIAN ELECTRONICS"

MATERIAL :		UNLESS OTHERWISE SPECIFIED: DIMENSIONS IN MM	
TOLERANCES :	XX ±0.20	ANGULAR : ±1°	DEBURR AND BREAK SHARP EDGES
	XXX ±0.10	FILLETS R/C : ±0.10	
	X.XXX ±0.01	SURFACE FINISH : Ra 1.6	
DRAWN	X.C.W	DATE	SIGNATURE
CHKD	H.Y.W	04/28/2022	
APPRVD	Q.L	04/28/2022	
MFG			

<p>LANJIAN ELECTRONICS 38 Hengtong Road, Xinqu Dingmao Zhenjiang, 212009, Jiangsu, P. R. China</p>		<p>1.0-KFD2-102023-1</p>	
<p>DWG No. GCPZ3.660.V.023-1</p>		<p>REV. A</p>	
<p>DO NOT SCALE THE DRAWING</p>		<p>1 / 1</p>	