


PRODUCT DATA SHEET



MATERIAL:
 BODY: STAINLESS STEEL
 CONTACT: BERYLLIUM COPPER
 INSULATOR: NORYL

PERFORMANCE:
 IMPEDANCE: 50 OHMS
 FREQUENCY: DC TO 18 GHz
 VSWR: ≤1.2

THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION THAT CANNOT BE REPRODUCED OR DIVULGED, IN WHOLE OR IN PART, WITHOUT WRITTEN AUTHORIZATION FROM "LANJIAN ELECTRONICS"

MATERIAL :		UNLESS OTHERWISE SPECIFIED: DIMENSIONS IN MM	
TOLERANCES :		ANGULAR : ±1°	
X.X	±0.20	FILETS R/C :	±0.10
X.XX	±0.10	SURFACE FINISH :	Ra 1.6
X.XXX	±0.01		
DRAWN	X.C.W	DATE	SIGNATURE
CHKD	H.Z.Y	04/21/2022	
APPRVD	H.Z.Y	04/21/2022	
MFG			
PROJECTION	SIZE	SCALE	
	A3	8:1	

LANJIAN ELECTRONICS
 38 Hengtong Road, Xinqu Dingmao
 Zhenjiang, 212009, Jiangsu, P. R. China

TITLE
3.5/N-KJ

DWG No. GCPZ3.640.F.020

DO NOT SCALE THE DRAWING

