



**MATERIAL:**  
 STAINLESS STEEL  
 BERYLLIUM COPPER  
 NORYL/PTFE

**PERFORMANCE:**  
 50 OHMS  
 DC TO 18GHz  
 ≤1.20

**BODY:**  
 STAINLESS STEEL

**CONTACT:**  
 BERYLLIUM COPPER

**INSULATOR:**  
 NORYL/PTFE

**IMPEDANCE:**  
 50 OHMS

**FREQUENCY:**  
 DC TO 18GHz

**VSWR:**  
 ≤1.20

THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION THAT CANNOT BE REPRODUCED OR DIVULGED, IN WHOLE OR IN PART, WITHOUT WRITTEN AUTHORIZATION FROM "LANJIAN ELECTRONICS"

MATERIAL :		UNLESS OTHERWISE SPECIFIED: DIMENSIONS IN MM	
TOLERANCES :		ANGULAR : ±1°	
XX	±0.20	FILETS R/C :	±0.10
XXX	±0.10	SURFACE FINISH :	Ra 1.6
X.XXX	±0.01		
DRAWN	X.C.W	DATE	SIGNATURE
CHKD	H.Z.Y	04/13/2021	
APPRVD	H.Z.Y	04/13/2021	
MFG			
PROJECTION	SIZE	SCALE	
	A3	8:1	

**LANJIAN ELECTRONICS**  
 38 Hengtong Road, Xinqu Dingmao  
 Zhenjiang, 212009, Jiangsu, P. R. China

TITLE  
 2.4/-JK

DWG No. GCP Z3, 640, 0.026

DO NOT SCALE THE DRAWING

REV. A

DATE 1 / 1