



MATERIAL:
 BODY: STAINLESS STEEL
 CONTACT: BERYLLIUM COPPER
 INSULATOR: PE I

PERFORMANCE:
 IMPEDANCE: 50 OHMS
 FREQUENCY: DC TO 26.5GHZ
 VSWR: ≤1.25

THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION THAT CANNOT BE REPRODUCED OR DIVULGED, IN WHOLE OR IN PART, WITHOUT WRITTEN AUTHORIZATION FROM "LANJIAN ELECTRONICS"

MATERIAL :		UNLESS OTHERWISE SPECIFIED: DIMENSIONS IN MM	
TOLERANCES :		ANGULAR : ± 1°	
XX	± 0.20	FILETS R/C :	± 0.10
XXX	± 0.10	SURFACE FINISH :	Ra 1.6
X.XXX	± 0.01	DEBURR AND BREAK SHARP EDGES	
DRAWN	X.C.W	DATE	11/24/2022
CHKD	H.Z.Y	DATE	11/24/2022
APPRVD	H.Z.Y	DATE	11/24/2022
MFG		SIGNATURE	
PROJECTION		SIZE	A3
		SCALE	4:1

LANJIAN ELECTRONICS
 38 Hengtong Road, Xinqu Dingmao
 Zhenjiang, 212009, Jiangsu, P. R. China

TITLE
3.5-JWK

DWG No. GCPZ3.640.F.034
 DO NOT SCALE THE DRAWING

REV.
 A
 1 / 1