



**MATERIAL:**  
 BODY: STAINLESS STEEL  
 CONTACT: BERYLLIUM COPPER  
 INSULATOR: NORYL  
**PERFORMANCE:**  
 IMPEDANCE: 50 OHMS  
 DC TO 18GHz  
 FREQUENCY: ≤1.20

STAINLESS STEEL  
 BERYLLIUM COPPER  
 NORYL

50 OHMS  
 DC TO 18GHz  
 ≤1.20

THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION THAT CANNOT BE REPRODUCED OR DIVULGED, IN WHOLE OR IN PART, WITHOUT WRITTEN AUTHORIZATION FROM "LANJIAN ELECTRONICS"

MATERIAL :		UNLESS OTHERWISE SPECIFIED: DIMENSIONS IN MM	
TOLERANCES :		ANGULAR : ± 1°	
X.X	± 0.20	FILETS R/C :	± 0.10
X.XX	± 0.10	SURFACE FINISH :	Ra 1.6
X.XXX	± 0.01		
NAME	DATE	SIGNATURE	
DRAWN X.C.W	08/25/2020		
CHKD H.Z.Y	08/25/2020		
APPRVD H.Z.Y	08/25/2020		
MFG			
PROJECTION	SIZE	SCALE	
	A3	8:1	

**LANJIAN ELECTRONICS**  
 38 Hengtong Road, Xinqu Dingmao  
 Zhenjiang, 212009, Jiangsu, P. R. China

TITLE  
**SMA/TNC-KJ**

DWG No. GCP ZJ, 640, A, 046  
 DO NOT SCALE THE DRAWING

REV. A  
 DATE 1 / 1