



MATERIAL:
 BODY: STAINLESS STEEL
 CONTACT: BERYLLIUM COPPER
 INSULATOR: NORYL
PERFORMANCE:
 IMPEDANCE: 50 OHMS
 DC TO 18GHZ
 FREQUENCY: ≤1.20

THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION THAT CANNOT BE REPRODUCED OR DIVULGED, IN WHOLE OR IN PART, WITHOUT WRITTEN AUTHORIZATION FROM "LANJIAN ELECTRONICS"

MATERIAL : UNLESS OTHERWISE SPECIFIED: DIMENSIONS IN MM		TOLERANCES :		ANGULAR : ±1°		DEBURR AND BREAK SHARP EDGES	
X.X ±0.20		X.XX ±0.10		X.XXX ±0.01		FILLETS R/C : ±0.10	
NAME		DATE		SIGNATURE			
DRAWN X.C.W		08/25/2020					
CHKD H.Z.Y		08/25/2020					
APPRVD H.Z.Y		08/25/2020					
MFG							
PROJECTION		SIZE		SCALE			
		A3		8:1			

LANJIAN ELECTRONICS
 38 Hengtong Road, Xinqu Dingmao
 Zhenjiang, 212009, Jiangsu, P. R. China

TITLE
SMA/TNC-KK

DWG No. GCP ZJ.640.A.047
 DO NOT SCALE THE DRAWING

REV. A
 1 / 1