



A向视图

MATERIAL:
 BODY: STAINLESS STEEL
 CONTACT: BERYLLIUM COPPER
 INSULATOR: PEI/PTEFE

PERFORMANCE:
 IMPEDANCE: 50 OHMS
 FREQUENCY: DC TO 40 GHZ
 VSWR: ≤1.30

THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION THAT CANNOT BE REPRODUCED OR DIVULGED, IN WHOLE OR IN PART, WITHOUT WRITTEN AUTHORIZATION FROM "LANJIAN ELECTRONICS"

MATERIAL : UNLESS OTHERWISE SPECIFIED: DIMENSIONS IN MM		TOLERANCES :		ANGULAR : ±1°		DEBURR AND BREAK SHARP EDGES	
XX	±0.20	XX	±0.10	XX	±0.10	XX	±0.10
XX	±0.10	XX	±0.01	XX	±0.01	XX	±0.01
NAME	DATE	SIGNATURE					
DRAWN	X.C.W	03/01/2022					
CHKD	H.Z.Y	03/01/2022					
APPRVD	H.Z.Y	03/01/2022					
MFG							
PROJECTION	SIZE	SCALE					
	A3	7:1					

LANJIAN ELECTRONICS
 38 Hengtong Road, Xinqu Dingmao
 Zhenjiang, 212009, Jiangsu, P. R. China

TITLE
2.92-KEL-635018P

DWG No.
 DO NOT SCALE THE DRAWING

REV.
 C

REV.
 1 / 1