



**MATERIAL:**  
 STAINLESS STEEL  
 BERYLLIUM COPPER  
 NORYL

**BODY:**  
 STAINLESS STEEL

**CONTACT:**  
 BERYLLIUM COPPER

**INSULATOR:**  
 NORYL

**IMPEDANCE:**  
 50 OHMS

**FREQUENCY:**  
 DC TO 9GHZ

**VSWR:**  
 ≤1.03

THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION THAT CANNOT BE REPRODUCED OR DIVULGED, IN WHOLE OR IN PART, WITHOUT WRITTEN AUTHORIZATION FROM "LANJIAN ELECTRONICS"

MATERIAL :		UNLESS OTHERWISE SPECIFIED: DIMENSIONS IN MM	
TOLERANCES :		ANGULAR : ±1°	
XX	±0.20	XX	±0.10
XXX	±0.10	XXX	±0.10
XXXX	±0.01	XXXX	±0.10
SURFACE FINISH : Ra 1.6		DEBURR AND BREAK SHARP EDGES	
NAME	DATE	SIGNATURE	
DRAWN	X.C.W	09/15/2020	
CHKD	H.Z.Y	09/15/2020	
APPRVD	H.Z.Y	09/15/2020	
MFG			
PROJECTION	SIZE	SCALE	
	A3	8:1	

**LANJIAN ELECTRONICS**  
 38 Hengtong Road, Xinqu Dingmao  
 Zhenjiang, 212009, Jiangsu, P. R. China

TITLE  
**N-JJ-9G**

DWG No. GCP ZJ,640,D.002

DO NOT SCALE THE DRAWING

REV. A

DATE 1/1