



**MATERIAL:**  
 BODY: STAINLESS STEEL  
 CONTACT: BERYLLIUM COPPER  
 INSULATOR: PE 1

**PERFORMANCE:**  
 IMPEDANCE: 50 OHMS  
 FREQUENCY: DC TO 26.5GHZ  
 VSWR: ≤1.15

THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION THAT CANNOT BE REPRODUCED OR DIVULGED, IN WHOLE OR IN PART, WITHOUT WRITTEN AUTHORIZATION FROM "LANJIAN ELECTRONICS"

|              |        |  |                         |
|--------------|--------|--|-------------------------|
| MATERIAL :   |        | UNLESS OTHERWISE SPECIFIED: DIMENSIONS IN MM |                         |
| TOLERANCES : |        | ANGULAR : ± 1°                               |                         |
| XX           | ± 0.20 | XX   | FILLETS R/C : ± 0.10    |
| XXX          | ± 0.10 | XXX  | SURFACE FINISH : Ra 1.6 |
| XXXX         | ± 0.01 | XXXX   | BREAK SHARP EDGES       |
| DRAWN        | X.C.W  | DATE   | SIGNATURE               |
| CHKD         | H.Z.Y  | 11/24/2022                                   |                         |
| APPVD        | H.Z.Y  | 11/24/2022                                   |                         |
| MFG          |        |  |                         |
| PROJECTION   | SIZE   | SCALE  |                         |
|              | A3     | 4:1  |                         |

**LANJIAN ELECTRONICS**  
 38 Hengtong Road, Xinqu Dingmao  
 Zhenjiang, 212009, Jiangsu, P. R. China

TITLE  
**NMD3.5/3.5-KJ**

DWG No. GCPZ3.640.F.029  
 DO NOT SCALE THE DRAWING

REV.  
 A  
 1 / 1