


PRODUCT DATA SHEET



MATERIAL:
BODY: STAINLESS STEEL
CONTACT: BERYLLIUM COPPER
INSULATOR: NORYL

PERFORMANCE:
IMPEDANCE: 50 OHMS
FREQUENCY: DC TO 26.5GHZ
VSWR: ≤ 1.2

THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION THAT CANNOT BE REPRODUCED OR DIVULGED, IN WHOLE OR IN PART, WITHOUT WRITTEN AUTHORIZATION FROM "LANJIAN ELECTRONICS"

MATERIAL :		UNLESS OTHERWISE SPECIFIED: DIMENSIONS IN MM	
TOLERANCES :		ANGULAR : $\pm 1^\circ$	
XX	± 0.20	XX	FILETS R/C : ± 0.10
XXX	± 0.10	XXX	SURFACE FINISH : Ra 1.6
XXXX	± 0.01		
DRAWN	X.C.W	DATE	SIGNATURE
CHKD	H.Z.Y	04/21/2022	
APPRVD	H.Z.Y	04/21/2022	
MFG			
PROJECTION		SIZE	SCALE
		A3	8:1

LANJIAN ELECTRONICS
38 Hengtong Road, Xinqu Dingmao
Zhenjiang, 212009, Jiangsu, P. R. China

TITLE
2.4/SMA-KK

DWG No. GCDZ3.640.A.032

DO NOT SCALE THE DRAWING

REV.
A
1 / 1