



MATERIAL:
 BODY: STAINLESS STEEL
 CONTACT: BERYLLIUM COPPER
 INSULATOR: PEI

PERFORMANCE:
 IMPEDANCE: 50 OHMS
 DC TO 40 GHZ
 FREQUENCY: ≤1.25

THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION THAT CANNOT BE REPRODUCED OR DIVULGED, IN WHOLE OR IN PART, WITHOUT WRITTEN AUTHORIZATION FROM "LANJIAN ELECTRONICS"

MATERIAL : UNLESS OTHERWISE SPECIFIED: DIMENSIONS IN MM		TOLERANCES :		ANGULAR : ±1°		DEBURR AND BREAK SHARP EDGES	
XX	±0.20	XX	±0.10	XX	±0.10	XX	±0.01
XX	±0.10	XX	±0.01	XX	±0.01	XX	±0.01
XX	±0.01	XX	±0.01	XX	±0.01	XX	±0.01
NAME	DATE	SIGNATURE					
DRAWN X.C.W	08/17/2022						
CHKD H.Z.Y	08/17/2022						
APPRVD H.Z.Y	08/17/2022						
MFG							
PROJECTION	SIZE	SCALE					
	A3	8:1					

LANJIAN ELECTRONICS
 38 Hengtong Road, Xinqu Dingmao
 Zhenjiang, 212009, Jiangsu, P. R. China

TITLE
1.0/2.92-KJ

DWG No. GCPZ3.640.V.025
 DO NOT SCALE THE DRAWING

REV.
 A

DATE
 1 / 1